

3710 excavatrice, compatible avec

2816 Gear Engine HP: 28 * MSRP: see Dealer for details



Tractor Overview

A proven, time-tested, high performance 4WD compact tractor for light-to medium-duty applications.

Tractor Key Uses

Home and Commercial Landscaping, Vegetable Gardening, Lawn and Grounds Maintenance, Light Construction

[MORE INFO](#) [SERIES PDF](#)

2816 HST Engine HP: 28 * MSRP: see Dealer for details



Tractor Overview

A proven, time-tested, high performance 4WD compact tractor for light-to medium-duty applications.

Tractor Key Uses

Home and Commercial Landscaping, Vegetable Gardening, Lawn and Grounds Maintenance, Light Construction

[MORE INFO](#) [SERIES PDF](#)

3316 Gear Engine HP: 33 * MSRP: see Dealer for details



Tractor Overview

A proven, time-tested, high performance 4WD compact tractor for light-to medium-duty applications.

Tractor Key Uses

Home and Commercial Landscaping, Vegetable Gardening, Lawn and Grounds Maintenance, Light Construction

[MORE INFO](#) [SERIES PDF](#)

3316 HST Engine HP: 33 * MSRP: see Dealer for details



Tractor Overview


A proven, time-tested, high performance 4WD compact tractor for light-to medium-duty applications.

Tractor Key Uses

Home and Commercial Landscaping, Vegetable Gardening, Lawn and Grounds Maintenance, Light Construction

[MORE INFO](#) [SERIES PDF](#)

Attachments > Backhoes > 3710 Backhoe



3710 Backhoe * MSRP: see dealer

Overview: Heavy-duty buckets with formed cutting edges and 3 horizontal wear bars. Mahindra's formed console gives unit a modern appearance and greater comfort to operator. Covered by a 2-year limited warranty.

Note - Instruction: Unhook the sway links from the rear axle brackets and remove 3 point hitch lower link arms, the sway links and the top link. This will prevent damage to tractor and backhoe.

[SPECS PDF](#) [PRINT](#)

*Pricing and programs (including Customer Price Reductions and Cash-in-lieu) may vary by state. Please contact your local dealer for more information.

FEATURES | SPECS | COMPATIBLE WITH

- Backhoe valve is positioned low to operator; this allows less heat and noise to be transferred into operator's area
- Dedicated hydraulic valve with dual axis levers
- Formed console gives unit a modern appearance and greater comfort to operator
- Heavy-duty swing frame
- High strength steel with double formed dipper arm
- SAE O-ring, Flat face O-ring, and JIC hydraulic connections are used to reduce potential hydraulic leaks
- Cushioned, orificed and port reliefs are designed into the swing cylinder circuit allowing for smooth operation of backhoe
- Double acting cylinders
- Heavy-duty buckets with formed cutting edges and 3 horizontal wear bars
- High back, comfortable seat
- Mahindra backhoes are covered by a two-year limited warranty
- Under frame Mounting System mounts to the center and rear end of tractor

TRANSPORT	
Boom Pivot Height	12"
Operating Weight w/ 12" Bucket (lbs.)	952
Overall Length	6' 7"
Transport Height (boom fully retracted)	9' 11"
Transport Width (stabilizers up)	5' 3"
OPERATIONAL	
Bucket Rotation	175°
Digging Depth (2 ft.) Flat Bottom	7' 8"
Digging Depth (8 ft.) Flat Bottom	6' 2"
Digging Depth Maximum	7' 10"
Digging Force - Bucket (lbs.)	2900
Digging Force - Dipper (lbs.)	1100
Loading Height	5' 3"
Loading Reach	4' 3"
Overall Operating Height - Fully Raised	10'
Reach from Swing Post	10' 7"
Stabilizer Down Below Grade	10"
Stabilizer Spread Operating Position	8' 5"
Swing Arc	180°
System Relief Valve Setting (PSI)	2050