

BACKHOES

WITH TRACTOR MODEL 4035 4WD SHUTTLE/PST/HST

Backhoe Models	485
----------------	-----

TRANSPORT

Shipping Weight with 12" bucket (lbs.)	1010
--	------

Transport Height (boom fully retracted)	81"
---	-----

Transport Width (stabilizers up)	51"
----------------------------------	-----

Boom Pivot Height	12"
-------------------	-----

Overall Length	83"
----------------	-----

OPERATIONAL

Maximum Digging Depth	101"
-----------------------	------

Digging Depth (2 Ft.) Flat Bottom	100"
-----------------------------------	------

Digging Depth (8 Ft.) Flat Bottom	52"
-----------------------------------	-----

Overall Operating Height - Fully Raised	121"
---	------

Loading Height	63"
----------------	-----

Loading Reach	58"
---------------	-----

Reach From Swing Post	127"
-----------------------	------

Bucket Rotation	180°
-----------------	------

Swing Arc	180°
-----------	------

Stabilizer Spread Operating Position	90"
--------------------------------------	-----

Stabilizer Down Below Grade	10"
-----------------------------	-----

System Relief Valve Setting	2750
-----------------------------	------

Digging Force - Bucket (lbs.)	3895
-------------------------------	------

Digging Force - Dipper (lbs.)	2358
-------------------------------	------