

MAHINDRA
6110
SHUTTLE CAB

STRONG & VERSATILE

59 ENGINE HP • 48.5 PTO HP

HEAVY-DUTY TRACTOR

Economical and easy to operate cab tractor designed for general purpose farming and ag, livestock operations and ground maintenance.

- # 1 selling tractor in the world
- 5-year powertrain warranty
- Attractive Financing Options
- Heavy-duty cast-iron chassis

- Professional grade components
- Japan Quality Medal Winner
- Deming Application Prize Winner
- Industry-leading parts support



 **Mahindra**
Rise.

TRACTOR 6110 SHUTTLE CAB

ENGINE	HST
Type	Turbo-charged, indirect injection
Cylinders	4
Engine HP (kW) @ rpm	59 (44) @ 2600
Compression Ratio	22:1
Displacement cubic inch (cc)	148.6 (2435)
Fuel Tank Capacity	18.5 gallons
ELECTRICAL	
Battery Capacity	12 volt, 80 amp hours
Alternator	12 volt, 50 amps
CLUTCH	
Type	Single plate, dry
TRANSMISSION	
Type	Sync. shuttle w/part. synchromesh
Number of Gears / Speeds	12F / 12R
FRONT WHEEL DRIVE	
Type	MFWD
STEERING	
Type	Hydrostatic/Tilttable
Pump Output (gallons per minute)	5.4
BRAKES	
Type	Wet disc
HYDRAULIC SYSTEM	
Type	Open center w/pos. & draft control
Pump Output (gallons per minute)	11
3-Point Linkage	Category 2, with telescopic stabilizers
Lift Capacity (lbs.)	3527
Rear Auxiliary Remote Valves	One standard
PTO	
Type	Independent
PTO RPM (engine rpm)	540
PTO HP (kW)	48.5 (36.2)
OPERATING WEIGHT	
Total (lbs.)	4850
DIMENSIONS With Industrial Tires	
Overall Length Inches (mm)	141.3 (3590)
Overall Width Inches (mm)	71.5 (1817)
Overall Height to top of cab Inches (mm)	99.2 (2520)
Turning Radius Minimum feet (meters)	12.5 (3.81)
TIRES Sizes & Options	
Ag (Front / Rear)	9.5x20 / 14.9x28
Industrial (Front / Rear)	10.5/80x18 / 18.4x24

LOADER ML161

WITH TRACTOR MODEL 6110 SHUTTLE CAB

Maximum Lift Height	115.4"
Clearance with Attachment Dumped	82.3"
Reach at Maximum Height	21.4"
Maximum Dump Angle	69°
Attachment Rollback Angle	39°
Digging Depth Below Grade	5.2"
Lift Capacity to Full Height @ Pivot Pins (lbs.)	2991
Breakout Force @ Pivot Pins (lbs.)	5225
Rated Flow (Tractor System)	11 gpm
Attachment Width used for specification	72"
Loader Shipping Weight (lbs.)	1318

CAB FEATURES

WITH TRACTOR MODEL 6110 SHUTTLE CAB

HVAC (Heating, Venting and A/C)	✓
Wide Opening Doors	✓
Semi-flat Platform	✓
Work Lights	2 Front/2 Rear
Entry/Exit Handles	✓
Large Glass Surface Area (clear 360 degree view)	✓
Side Mirrors	✓
Cup Holder	✓
Excellent Headroom and Visibility	✓

