

MAHINDRA TRACTORS

Attachments > Mowers > 72" Mid-Mount Mower



72" Mid-Mount Mower

MSRP: see Dealer

Overview: Heavy-duty mid-mount mowers from Mahindra are designed to handle the toughest of your cutting jobs.

; include mower, bracket kit and mid-PTO kit. Mid-PTO kit is not required on some models, please contact your dealer for more information.

[Specs](#)

FUNCTIONAL SPECIFICATIONS	
Blade Speed (RPM)	2463
Blade Thickness x Width (in.)	.25 x 2.5
Blade Tip Speed (ft/min)	15900
Cutting Height Range (in.)	1 - 4
Cutting Width (in.)	72
Front Wheel Size (in.)	3.5 x 8
Front Wheels Pivot	Standard
Ground Clearance - Transport (in.)	6.75 on 2615, 2615HST, 3015HST; 5.75 on 2815HST, 3215HST
Number of Blades/Spindles	3
Number of Wheels	4
Rear Wheel Size (in.)	3.5 x 8
Tractor Mid-PTO Speed (RPM)	2000
Universal Drive	0600
Weight of Deck Assembly (lbs.)	400
SAFETY & CONVENIENCE FEATURES	
Discharge Chute Retention	Pin, Spring & Wingnut
Front Height Adjustment	Easy Access Pin & Shaft
Mower Transport Lock for 3-Point Use	Standard
Rear Height Adjustment	Easy Access Pin & Shaft
Spindle Wrench for Blade Removal	Standard
PERFORMANCE FEATURES	
Front Anti-Scalp Roller	Standard
Mower Deck Depth - Front (in.)	6.63
Mower Deck Depth - Rear (in.)	3.63
Rear Anti-Scalp Roller	N/A
RELIABILITY & DURABILITY FEATURES	
Blade Spindle Bearings	Tapered Roller
Blade Spindle Housing	Cast Iron
Drive Belt Section	Double "B"
Driven Sheave Construction	Cast, Machined
Driven Sheave Retention	Tapered Bushing

Driver Sheave Construction	Cast, Machined
Driver Sheave Retention	Tapered Bushing
Gearbox Housing	Cast Iron, Finned
Gearbox Manufacturer	Woods
Idler Sheave Construction	Cast, Machined
Idler Sheave Retention	Bolt
Mower Deck Construction	1 piece
Mower Deck Thickness (in.)	0.164